


SIZE	A	B	C	D	F	G	H	W	ACT.
1/2	167	146			80	62		96	R0
3/4	167	146			89	73		96	R0
1	167	146			105	84		96	R0
1 1/4	168	200			113	92		105	R1
1 1/2	168	200			140	110		105	R1
2	168	200			161	118		105	R1

SPECIFICATIONS			
VALVE		ELECTRIC ACTUATOR	
BODY	Stainless steel	PROTECTION RATING	IP65 (Weatherproof)
SEATS	PTFE	VOLTAGES	12, 24DC 24, 110, 240 AC
SEALS	PTFE	MANUAL OVERRIDE	Standard Across Range
ENDS	BSPP	VOLT FREE CONTACTS	Standard Across Range(2-off)
 <div style="border: 1px solid red; padding: 2px; font-size: 8px; color: red; display: inline-block;">           All Dimensions In mm.            Uncontrolled Copy,            Not Subject To            Automatic Update            E&amp;OE         </div>		VISUAL INDICATOR	Standard Across Range
		DUTY RATING	35%
		ON POWER FAILURE	Stays put
		CONNECTION	All external by Din plug

## STAINLESS STEEL 3-WAY BALL VALVE WITH MODULATING ACTUATOR

**J+J**  
ACTUATORS

Drawn By  
MRG

Chk  
DC

File Name  
2305

Scale  
NTS

Dwg No. 2305

Revision  
1

Sheet  
1/1

Date  
06/01/01