


SIZE	A	B	C	D	F	G	H	W	ACT.
1/2	168	146	63	46	84	64	255	96	U0
3/4	168	146	63	46	108	64	255	96	U0
1	168	146	73	56	124	86	275	96	U0
1 1/4	168	146	73	56	142	86	275	96	U0
1 1/2	168	146	85	74	167	116	305	96	R0
2	168	146	85	74	198	121	305	96	R0
2 1/2	168	200	121	108	323	174	429	105	R1
3	168	200	121	108	269	179	429	105	R1
4	168	200	121	108	269	179	429	105	R1

SPECIFICATIONS			
VALVE		ELECTRIC ACTUATOR	
BODY	PVC	PROTECTION RATING	IP65 (Weatherproof)
SEATS	PTFE	VOLTAGES	12, 24DC 24, 110, 240 AC
SEALS	EPDM (Viton option)	MANUAL OVERRIDE	Standard Across Range
ENDS	BSP/ plain socket	VOLT FREE CONTACTS	Standard Across Range(2-off)
 <div style="border: 1px solid red; padding: 2px; font-size: 8px; color: red; display: inline-block;"> All Dimensions In mm. Uncontrolled Copy, Not Subject To Automatic Update E&OE </div>		VISUAL INDICATOR	Standard Across Range
		DUTY RATING	35%
		ON POWER FAILURE	Stays put
		CONNECTION	All external by Din plug

P.V.C. BALL VALVE WITH MODULATING ACTUATOR

J+J
ACTUATORS

Drawn By
MRG

Chk
DC

File Name
3105_1

Scale
NTS

Dwg No.

3105/1

Revision
1

Sheet
1/1

Date
06/01/01