


SIZE	A	B	C	D	E	F	G	H	W	ACT.
2	167	195	104	66	15		43	380	104	J2-20DPS
2 1/2	167	195	122	76	15		46	408	104	J2-55DPS
3	167	195	142	93	15		46	445	104	J2-55DPS
4	235	252	154	112	15		52	533	214	J2-140DPS
5	235	252	170	122	15		56	559	214	J2-140DPS
6	235	252	177	140	15		56	584	214	J2-140DPS
8	235	252	213	172	15		60	652	214	J2-300DPS
10	235	252	264	203	15		68	734	214	J2-300DPS
12	235	252	314	231	15		78	812	214	J2-300DPS
		T	Y	P	I	C	A	L		

SPECIFICATIONS			
VALVE		ELECTRIC ACTUATOR	
BODY	Coated Cast/ Ductile Iron	PROTECTION RATING	IP65 (Weatherproof)
DISC	CI/ AlI Bze or Stainless	VOLTAGES	12DC to 240V AC
LINER	EPDM/ BUNA/ Viton/ Silicone	MANUAL OVERRIDE	Standard Across Range
ENDS	To suit PN10/16	VOLT FREE CONTACTS	Standard Across Range (2-off)
 <div style="font-size: small; text-align: center;"> All Dimensions In mm. Uncontrolled Copy, Not Subject To Automatic Update E&OE </div>		VISUAL INDICATOR	Standard Across Range
		DUTY RATING	75%
		ON POWER FAILURE	Stays put
		CONNECTION	All external by Din plug

C.I. BUTTERFLY VALVE WITH MODULATING ELECTRIC ACTUATOR

MODULATING ACTUATOR

Drawn By
MRG

Chk
DC

File Name
6105J2

Scale
NTS

Dwg No.

6105J2

Revision
1

Sheet
1/1

Date
12/05/00